



UERTICAL TURBINE PUMP CURUES

1160 24.1



Vertical Turbine Pump Curves 1160 TABLE OF CONTENTS

For more information, or the location of your nearest SIMFLO distributor, please visit www.simflo.com

> Texas: 2605 Interstate 27 Lubbock, TX 79404 806.747.3411

Arizona: 754 E. Maley St. Willcox, AZ 85643 520.384.2273 Mississippi: 8500 Aaron Lane Southaven, MS 38671 662.793.8090

Terms and Conditions	i-ii
General Information	Section 100
Turbine Performance	Section 200
11/0 DDM	Section 202

SIMFLO, LLC. Terms and Conditions

SIMFLO, LLC. is herein referred to as the "Seller" and the customer purchasing goods ("Goods") from the Seller is referred to as the "Buyer." The Terms and Conditions as set forth herein, and the Seller's quotation, estimate or bid to Buyer, shall collectively and exclusively govern all of the rights, duties and obligations of Seller and Buyer related to Buyer's purchase order for the Goods Seller is agreeing to sell to Buyer. Any terms and conditions set forth in Buyer's purchase order which are different or inconsistent with Seller's Terms and Conditions and/or Seller's quotation, estimate or bid, shall be null and void. Buyer's receipt of the Goods, and/or payment, or partial payment, to Seller for the Goods being sold to Buyer, shall evidence Buyer's acceptance of the terms and conditions of the sale as set forth herein. Seller reserves the right, in its sole discretion, to refuse any purchase order.

- 1. PRICES: Prices for Goods shall apply to the specific quantities stated in Seller's quotation, estimate or bid. Prices shall include standard packing according to Seller's specification for packing and delivery. All costs and taxes for special packing requests by Buyer, including packing for exports, shall be paid by Buyer as an additional charge. Prices for Goods are subject to change without notice based on any subsequent changes in the cost to Seller for sub-supplier materials, supplies or other related increases, and the adjusted price will be based on the cost to Seller in effect at the time of the requested shapment date, and each shipment will be invoiced at such increased price. All prices for Goods are exclusive of, and do not include, any applicable sales, use, existe, GST, VAT or similar taxes, duties or levies, or transportation or insurance costs, and all such costs are the sole responsibility of, and shall be paid by, Buyer.
- 2. TAXES. Any current or future tax or government charge, or increase in same, affecting Seller's costs of production, sales, delivery or shipment, or which Seller is otherwise required to pay or collect in connection with the sale, purchase, delivery, storage, processing, use of consumption of Goods, shall be paid by Buyer and shall either be added to the purchase price of the Goods or billed to Buyer separately, at Seller's election.
- 3. ARBITRATION: Seller and Buyer agree that any controversy or claim, excluding collections and past due accounts, arising out of or relating to the agreed terms as provided herein to sell Goods, or the breach thereof, shall be submitted to mandatory relibration in accordance with the Texas Arbitration Act, and the arbitration award or dispositive order, shall be find and binding and may be entired in any court of competent jurisdiction in the State of Texas. The exclusive place of arbitration shall be within Lubbock County, Texas, and the parties hereby submit to such jurisdiction and venue. Collections and past due accounts may be filed in the appropriate court located in Lubbock County, Texas, and Buyer hereby submits to the exclusive jurisdiction and venue in Lubbock County, Texas.
- 4. TERMS OF PAYMENT: Seller reserves the right to require payment in advance or C.O.D., and otherwise modify credit terms should Buyer's credit standing not meet Seller's credit requirements. Unless otherwise specified in writing by Seller, the terms of payment are net thirty (30) days from the date of Seller's invoice to be paid in U.S. currency. All resistables are subject to prior approval by Seller. Seller may, at its option, require copies of perfinent contracts, financial statements and other documents relative to any given sate of Goods in order to evaluate and determine, in its sole discretion, Buyer's credit status or the credit status of any third party with whom Buyer has a contractual relationship concerning the Goods to be furnished to Buyer. Failure or delay in delivery of this information will postpone production and delivery of Goods, and may result in a price increase. In the event payment is not made when due, Buyer agrees to pay Seller a service or finance charge of the lessor of: (i) one and one-half percent (1.5%) per month (18% per annum); or (ii) the highest rate permitted by applicable law, on the unpaid balance of the invoice from and after the invoice due date. Buyer shall be responsible for all costs and expenses associated with any checks returned due to insufficient funds. If, during the performance hereunder with Buyer, the financial responsibility or condition of Buyer is such that Seller in good faith deems itself insecure, or fi Buyer becomes insolvent, or if a material change in the ownership of Buyer cours, or if Buyer falls to make any payments in a dordance with the terms as provided herein, hen, in any such event, Seller is not obligated to continue performance under the agreed terms as provided herein, and may stop Goods in transit and defer or decline to make delivery of Goods, except upon receipt of satisfactory security or cash payments in advance, or Seller may terminate Buyer's purchase order upon written notice to Buyer without further obligation to Buyer whatsoever.
- 5. Quotation, (Estimate or Bid), Withdrawal, Expiration. Quotations, estimates or bids are valid for thirty (30) calendar days from the date of issuance, unless otherwise provided therein. Seller reserves the right to cancel or withdraw any quotation, estimate or bid at any time, with or without notice or cause, prior to acceptance by Buyer. There is agreement if any conditions specified within the quotation, estimate or bid are not completed by Buyer to Seller's satisfaction within thirty (30) calendar days of Seller's written acknowledgement of a purchase order by Buyer. Seller, nevertheless, reserves its right to accept any contractual documents received from Buyer after this 30-day perior.
- 6. SELLER'S RIGHTS IN DEFAULT: In the event Buyer fails to make any payment when due, Seller shall have the right, among other remedies, either to terminate its agreement with Buyer, or suspend further performances under the agreed terms a provided herein and/or any other agreements with Buyer. Buyer shall be liable for all expenses, including atomeys' fees, relating to the collection of past due amounts. Additionally, upon any payment default by Buyer, Buyer shall immediately pay to Seller the entire unpaid amounts for any and all shipments made to Buyer irrespective of the terms of said shipment whether said shipments made to Buyer irrespective of the terms of said shipment betheren Seller and Buyer, and Seller may also withhold all subsequent shipments until the full amount due is paid by Buyer. Acceptance by Seller of less than full payment shall not be a waiver of any of its rights hereunder. Buyer shall not assign or transfer its rights, duties or obligations, or any interest in it, or monies payable under it, without the written consent of Seller, and any assignment made without such written consent shall be null and void.
- 7. SHIPMENT AND DELIVERY: While Seller will use all responsible commercial efforts to maintain the delivery date(s) acknowledged or quoted by Seller, all shipping dates are proximate and not guaranteed. Shipment dates are best, setsimates only at the time of the proposal, and are subject to change based on manufacturing load and sub-supplier schedules at Seller's date of order and/or full release to manufacture. Seller reserves the right to make partial shipments. Seller, at its option, shall not be bound to tender delivery of any Goods postponed or delayed by Buyer for any reason. Buyer agrees to reimburse Seller for any and all strange costs and other additional expenses resulting thereform. Risk of loss and legal title to the Goods shall transfer to Buyer for sales in which the end destination of the Goods is outside the United States immediately after the Goods have passed beyond the territorial limits of the United States. For all other shipments, risk of loss for damage and responsibility shall pass from Seller to Buyer upon delivery to and receipt by a carrier at Seller's shipping point. All shipments are F. O.B. Seller's shipping point. Any dains for shortages or damages suffered in transit are the responsibility of the Buyer and shall be submitted by Buyer directly to the carrier. Shortages or damages must be identified and signed for at the time of delivery. Seller is not responsible for any such shortages or damages must be identified and signed for at the time of delivery. Seller is not responsible for any such shortages or damages must be identified and signed for at the time of delivery. Seller is not responsible for any such shortages or damages must be identified and signed for at the time of delivery incidental or consequential in nature, including without limitation loss of profits or liquidated damages, arising out of or relating to any failure of the Goods to be delivered by the specified delivery date. In the absence of specific instructions, Seller will select the carrier. Buyer shall reim
- 8. LIMITED WARRANTY: Subject to the limitations of Section 9, below, Seller warrants that the Goods manufactured by Seller will be free from defects in material and workmanship at the time of shipment

under normal use and regular service and maintenance, for a period of eighteen (18) months from the date of shipment of the Goods by Seller, or one year from start-up, whichever occurs first, unless otherwise specified by Seller in writing. Products and Special Coating Applications purchased by the Seller from a third party for resale to Buyer (*Resale Products*) shall cany only the warranty extended by the original manufacturer or supplier. ANY ITEM OF THE PRODUCT(S) WHICH IS NOT MANUFACTURED OR APPLED BY SELLER IS NOT WARRANTED BY SELLER and shall be covered not by the express warranty, if any, of the manufacturer or applicator thereof. THE WARRANTY SET FORTH IN THIS SECTION 8 AND THE WARRANTY SET FORTH IN THIS SECTION 8 AND THE WARRANTY SET FORTH IN THIS SECTION 9. BELOW, ARE THE SOLE AND EXCLUSIVE WARRANTES GIVEN BY SELLER WITH RESPECT TO THE GOODS, AND ARE IN LIEU OF AND EXCLUDE ALL OTHER WARRANTES, EXPRESS OR IMPLIED, ARISING BY OPERATION OF LAW OR OTHERWISE, INCLUDING WITHOUT LIMITATION, MERCHANTABLITY AND FITHESS FOR A PARTICULAR PURPOSE, WHETHER OR NOT THE PURPOSE OR USE HAD BEEN BECLOSED TO SELLER IN SPECIFICATIONS, DRAWINGS OR OTHERWISE, AND WHETHER OR NOT SELLERS GOODS ARE SPECIFICALLY DESIGNED AND/OR MANUFACTURED BY SELLER FOR BUYER'S USE OR PURPOSE. This warranty does not extend to any losses or damages due to misuse, accident, abuse, neglect, normal wear and bear, negligence (other than Seller's), unauthorized modification or alteration, use beyond rated capacity, unsuitable power sources or environmental conditions, improper installation, repair, handing, maintenance or application or any other cause not the fairly of the Seller. To the extent that Buyer, or its agents, has supplied specifications, information, representation of operating conditions or other data to Seller in the selection or design of the Goods and the preparation of Seller's quotation, estimate or bid, or in the event that actual operating conditions or other conditions differ from those represented by Buyer, any warranties or

Buver agrees to provide any subsequent transferee of the Goods conspicuous, written notice of Section 8 and 9 herein. Sections 8 and 9 shall apply to any entity or person who may buy, acquire or use the Goods, including any entity or person who obtains Goods from Buver, and such entity or person shall be bound by the limitations as provided herein.

- 9. LIMITATION OF REMEDY AND LIABLITY: BUYER'S SOLE AND EXCLUSIVE REMEDY FOR BREACH OF ANY WARRANTY HEREUNDER SHALL BE LIMITED TO REPAIR, CORRECTION, REPLACEMENT OR REFUND OF THE PURCHASE PRICE UNDER SECTION 8. SELLER SHALL NOT BE LIABLE FOR DAMAGES CAUSED BY DELLAY IN PERFORMANCE, AND THE REMEDIES OF BUYER UNDER THE AGREED TERMS AS PROVIDED HEREN ARE EXCLUSIVE. IN NO EVENT, REGARDLESS OF THE FORM OF THE CLAIM OR CAUSE OF ACTION (WHETHER BASED IN CONTRACT, INFRINGEMENT, NEGLIGENCE, STRICT LIABLITY, ANY OTHER TORT OR OTHERWISE), SHALL SELLER'S LIABLITY TO BUYER ANDIOR ITS CUSTOMERS EXCEED THE PRICE PAID BY BUYER FOR THE SPECIFIC GOODS PROVIDED BY SELLER GIVING RISE TO THE CLAIM OR CAUSE OF ACTION. BUYER AGREES THAT NO EVENT SHALL SELLER'S LIABLITY TO BUYER ANDIOR ITS CUSTOMERS EXTEND TO INCLIDE LIQUIDATED, INCIDENTAL, CONSEQUENTIAL, PUNITIVE, EXEMPLARY OR SPECIAL DAMAGES, INCLUDING BUT NOT LIMITED TO, LOSS OF PROFITS OR ANTICIPATED PROFITS, LOSS OF ANTICIPATED SAVINGS OR REVENUE, LOSS OF INCOME, LOSS OF PRODUCTION, ANDIOR LOSS OR DAMAGE TO PROPERTY OR EQUIPMENT. THE FOREGOING LIMITATIONS OF LIABLITY THAT HALL BE EFFECTIVE WITHOUT REGARD TO SELLER'S ACTS OR OMSSIONS ON REGLEGANCE OR STRICT LIABLITY IN THE PERFORMANCE OR NON-PERFORMANCE HEREUNDER. It is expressly understood that any technical advice fumished by Seller with respect to the use of the Goods is given without chappe, and Seller assumes no obligation or liability for the advice given, or result oblained, and all such advice being given is accepted at Buyer's risk.
- 10. Buyer Warranty: Buyer warrants the accuracy of any and all information relating to the details of its operating conditions, including temperatures, pressures, and where applicable, the nature of all hazardous materials. Seller can justifiably rely upon the couracy of Buyer's information in its performance. Should Buyer's information prove inaccurate, Buyer agrees to reimburse Seller for any losses, labilities, damages and expenses that Seller may have incurred as a result of any inaccurate information provided by Buyer to Seller.
- 11. EXCUSE OF PERFORMANCE/FORCE MAJEURE: Seller shall not be liable for delays in performance or for nonperformance due to acts of God; acts of Buyer, war, fire; flood; weather, natural disasters; terrorism; sabotage; strikes; labor
 disputes; civil disturbances or riots; currency restrictions; pandemics; disease; governmental requests, restrictions, allocations,
 laws, regulations, orders or actions; unavailability of or delays in transportation or in obtaining materials, thet, power and energy,
 default of suppliers; or unforeseen circumstances or any events or causes beyond Seller's reasonable control. Deliveries or
 other performances may be suspended for an appropriate period of time or canuseted by Seller upon notice buyer in the event
 of any occurrence of the foregoing, but the balance of the agreement shall otherwise remain unaffected as a result of the
 foregoing. If Seller determines that its ability to supply the total demand for the Goods, or to obtain material used directly or
 indirectly in the manufacture of the Goods, is induced, limited or made impracticable due to causes set forth hereinabove,
 Seller may allocate its available supply of the Goods or such material (without obligation to acquire other supplies of any such
 Goods or material) among itself and its buyers on such a basis as Seller determines to be equitable, in its sole discretion,
 without liability for any failure of performance which may result therefrom.
- 12. CANCELLATION: Except as otherwise provided herein, no order may be cancelled on special or made-to-order Goods unless requested in writing by either party and accepted in writing by the other party. In the event of a cancellation by Buyer, Buyer shall, within thirty (30) days of such cancellation, pay Seller a cancellation fee, which shall include all costs and expenses incurred by Seller prior to the receipt of the request for cancellation, including but not limited to, all commitments to its suppliers, subcontractors and others, all fully burdened labor and overhead expended by Seller, plus a reasonable profit charge. Return of Goods shall be in accordance with Seller's most current return policy and subject to a minimum thirty percent (30%) restocking fee, unless otherwise agreed to by the parties in writing. Notwithstanding anything to the contrary herein, in the event that (i) there is a commencement by or against Buyer of any voluntary or involuntary proceedings in bankrupty or insolvents, iii) its determined Buyer is insolvent, (iii) Buyer makes a general assignment for the benefit of its creditors; (iv) a receiver is appointed on account of Buyer's insolvency, (i) it is determined Buyer does not correct or, if immediate correction is not possible, commence and diligently continue action to correct any default of Buyer to comply with any of the provisions or requirements of the agreed terms as provided herein within ten (10) calendar

days after being notified in writing of such default by Seller, Seller may, by written notice to Buyer, without prejudice to any other rights or remedies which Seller may have, terminate its further performance hereunder. In the event of such terminate, Seller shall be entitled to receive payment as if Buyer has cancelled its purchase order pursuant to this paragraph. Seller may nevertheless elect to complete its performance of under the agreed terms provided herein by any means it chooses. Buyer agrees to be responsible for any additional costs incurred by Seller in so doing. Upon termination of the agreed terms as provided herein, the rights, obligations and liabilities of the parties, which shall have arisen or been incurred hereunder prior to its termination. Ashall survive such termination.

13. CHANGES: Buyer may request changes or additions to the Goods consistent with the Seller's specifications and criteria. In the event Seller accepts such changes or additions, Seller may revise the price and dates of delivery. Seller reserves the right to change the design and specifications for the Goods without prior notice to the Buyer, except with respect to Goods being made-to-order for Buyer. Seller shall have no obligation to install or make such change in any Goods manufactured prior to the date of notification of such change.

14. NUCLEAR, FIRE SYSTEMS, MEDICAL, LIFE-SUPPORT AND RELATED APPLICATIONS. Buyer accepts Goods with ANY NUCLEAR, FIRE SYSTEMS, MEDICAL, LIFE-SUPPORT AND RELATED APPLICATIONS. Buyer accepts Goods with oregoing understanding, and agrees to communicate same in writing to any subsequent purchasers or users, and to defend, indermity and hold harmless Seller for any claims, losses, suits, judgments and damages, including incidental and consequential damages, arising from such use, whether the cause be based in fort, contract or otherwise, including allegations that the Seller's liability is based on negligence or strict liability.

15. ASSIGNMENT: Buyer shall not assign its rights or delegate its duties hereunder, or any interest herein, without the prior written consent of Seller, and any such assignment, without such consent, shall be null and void.

16. INSPECTION/TESTING: Buyer shall have the right to inspect the Goods upon their receipt. When delivery is to Buyer's site or to a project site (Site*), Buyer shall notify Seller in writing of any nonconformity of the Goods with countries, estimate or bid, or the agreed terms as provided herein, within three (3) days from receipt of the Goods by Buyer, unless a shorter period is required in Seller's quotation, estimate or bid. For all other deliveries, Buyer shall notify Seller in writing of any nonconformity of the Goods with the quotation, estimate or bid. For all other deliveries, Buyer shall notify Seller in writing of any nonconformity of the Goods with the quotation, estimate or bid, or the agreed terms as provided herein, within fourteen (14) days from receipt of the Goods by Buyer. Failure to give such applicable notice shall constitute a waiver of Buyer's right to inspect and/or reject the Goods for nonconformity, and shall be equivalent to an irrevocable acceptance of the Goods by Buyer. Claims for loss of or damage to Goods in transit must be made to the carrier, and not to Seller. Buyer, at its option and sole expense, may inspect and observe the testing by Seller of the Goods for compliance with Seller's standard test procedures prior to shipment, which inspection and testing shall be conducted at Seller's plant at such reasonable time as determined by Seller. Any rejection of the Goods must be made promptly by Buyer before shipment. Tests shall be deemed to be satisfactorily completed, and the test fully met, when the Goods meet Seller's criteria for such procedures. Acceptance by Buyer, or Buyer's representative, of any witnessed testing or coatings will preclude any future rejection.

17. STANDARD, TOLERANCE: Except for made-to-order Goods specified by the Buyer in writing and expressly agreed to in writing by Seller, all Goods turnished hereunder are produced in accordance with the standard manufacturing practices in the control of origin of the Goods. All materials incorporated into the Goods are subject to mill oblerances and variations consistent with normal manufacturing practices for dimension, weight, straightness, section, composition and mechanical properties, normal surface and internal conditions, and deviations in quality resulting from practical testing. Seller is not responsible for any deterioration in quality as a result of the foregoing tolerances and variations.

18. DRAWINGS: Seller's prints and drawings (including without limitation, the underlying technology) furnished by Seller to Buyer in connection with Seller's quotation, estimate or bid are the property of Seller, and Seller retains all rights, including without limitation, exclusive rights of use and license. Buyer shall return all copies (in whatever medium) of such prints or drawings to Seller immediately upon request by Seller. Seller does not supply detailed or shop working drawings of the Goods; however, Seller will supply necessary installation drawings. The drawings and butler illustrations submitted with Seller quotation, estimate or bid, show general type, arrangement and approximate dimensions of the Goods to be turnished for Buyer's information only, and Seller makes no representation or warranty regarding their accuracy. Unless expressly stated to the contrary within the quotation, estimate or bid, all drawings, illustrations, specifications or diagrams form no part of the agreed terms as provided herein. Seller reserves the right to alter such details in design or arrangement of its Goods which, in its sole discretion, constitute an improvement in construction, application or operation of the Goods. All engineering information necessary for installation of the Goods shall be flowarded by Seller to Buyer at the time the Goods are shipped. After Buyer's acceptance of Seller's quotation, estimate or bid, any changes requested by Buyer in the type of Goods, the arrangement of the Goods, or the application of the Goods will be made at Buyer's expense. Instructions necessary for installation, operation and mention and the Goods and be formed to the Goods are been governed to the Goods and Buyer in the type of Goods, the arrangement of the Goods, or the application of the Goods will be made at Buyer's expense. Instructions necessary for installation, operation and mention and the Goods are beinged.

19. EXPORT/IMPORT: Buyer agrees that all applicable import and export control laws, regulations, orders and requirements, including without limitation those of the United States and the European Union, and the jurisdictions in which the Seller and Buyer are established, or from which the Goods may be supplied, will apply to the Goods receipt and use. In no event shall Buyer use, transfer, release, import or export any Goods in violation of such applicable laws, regulations, orders or requirements. The Buyer shall not, and shall not permit any third parties to, directly or indirectly, export, re-export or release any Goods to any jurisdiction or country to which, or any party to whom, the export, re-export or release of any Goods is prohibited by applicable law, regulation or rule. The Buyer shall be solely responsible for any breach of this Section 19.

20. Proprietary Information, Injunction: Seller's designs, illustrations, drawings, specifications, technical data, catalogues, to-know-how", economic or other business or manufacturing information (collectively "Proprietary Information") disclosed Buyer shall be deemed proprietary and confidential to Seller's Buyer agrees not to disclose, use or reproduce any Proprietary Information without first having obtained Seller's express written consent. Buyer's agreement to refrain from disclosing, using or reproducing Proprietary Information shall survive completion of the work and delivery of the Goods under the agreed terms a provided herein. Buyer acknowledges that its improper disclosure of Proprietary Information to any third party will result in Seller's suffering irreparable harm. Seller may seek injunctive or equilable relief to prevent Buyer's unauthorized disclosure of

21. Installation and Start-up: Unless otherwise agreed to in writing by Seller, installation of the Goods shall be the sole responsibility of Buyer. In the event Buyer has engaged Seller to provide an engineer for start-up supervision, such engineer will function in a supervisory capacity only, and Seller shall have no responsibility for the quality of workmanship of the installation. Buyer understands and agrees that it shall furnish, at Buyer's sole expense, all necessary foundations, supplies, labor and facilities that might be required to install and operate the Goods.

22. NSURANCE: Buyer agrees to do all acts necessary to protect Seller's interest by adequately insuring the Goods against loss or damage from any external cause, with Seller named as insured, additional insured or co-insured. Seller and Buyer agree to maintain liability insurance in commercially reasonable amounts covering claims of any kind or nature for damage to property or personal injury, including death, made by anyone that may arise from activities performed or facilitated related to the Goods, whether these activities are performed by that company, its employees, agents, or anyone directly engaged or employed by that party or its agents.

23. GENERAL PROVISIONS: These terms and conditions herein supersede all other communications, negotiations, and prior oral or written statements regarding the subject matter of the agreed terms as provided herein. No change, modification rescission, discharge, abandonment, or waiver of these terms and conditions shall be binding upon the Seller, unless made in writing and signed on its behalf by a duly authorized officer of Seller. No conditions, usage of trade, course of dealing or performance, understanding or agreement purporting to modify, vary, explain, or supplement these terms and conditions shall be binding unless hereafter made in writing and signed by the party to be bound, and no modification or additional terms shall be applicable to the agreed terms as provided herein by Seller's receipt, acknowledgement, or acceptance of purchase orders, shipping instruction forms, or other documentation containing terms at variance with or in addition at these set forth herein. Any such modifications or additional terms are specifically rejected and deemed a material alteration hereof. If this document

shall be deemed an acceptance of a prior offer by Buyer, such acceptance is expressly conditional upon Buyer's assent to any additional or different term set forth herein. There is no waiver by either party with respect to any other breach or default of any other right or memely, unless such waiver be expressed in witting and signed by the party to be bound. All typographical or clerical errors made by Seller in any quotation, estimate or bid, acknowledgement or publication are subject to correction. No action, regardless of form, arising out of transactions relating to this contract, may be brought by either party more than two years after the cause of action has accrued.

24. GOVERNING LAW: THE AGREED TERMS AS PROVIDED HEREIN, AND THE VALIDITY, PERFORMANCE, AND ALL OTHER MATTERS RELATING TO THE INTERPRETATION AND EFFECT OF AND ALL RIGHTS AND OBLIGATIONS HEREUNDER, SHALL BE GOVERNED BY THE LAWS OF THE STATE OF TEXAS, WITHOUT REFERENCE TO PRINCIPLES OF CONFLICTS OF LAW. SUBJECT TO THE ARBITRATION PROVISION AS PROVIDED HEREINABOVE, THE JURISDICTION OF ANY PROCEEDING RELATED TO THE GOODS SHALL BE IN THE STATE OF TEXAS AND VENUE SHALL BE LUBBOCK COUNTY, TEXAS. THE RIGHTS AND OBLIGATIONS OF THE PARTIES HEREUNDER SHALL NOT BE GOVERNED BY THE 1980 U.N. CONVENTION ON CONTRACTS FOR THE INTERNATIONAL SALE OF GOODS.

25. Titles: The section titles herein are for reference only, and shall not limit or restrict the interpretation or construction of this Agreement

26. Walver: Seller's failure to insist, in any one or more instances, upon Buyer's performance of this Agreement, or to exercise any rights conflered, shall not constitute a walver or relinquishment of any such right or right to insist upon Buyer's performance in any other regard.

27. Severability: The partial or complete invalidity of any one or more provisions of this Agreement shall not affect the validity or continuing force and effect of any other provision.



1160, 880 & 700 **Pump Model Designation** and Cross Reference

SIMFLO	Simmons Pump	Simflo Pump
SR11MO	SR13M	SN12S
SR11HO	SR13H	ST12S
SP11L (1)	SM13L	SP12C
SP11M (1)	SM13M	SR12C
SP11H (1)	SM13H	SV12C
SW12L (1,2)	SW12L	SC12C
SW12M (1,2)	SW12M	SD12C
SL12M (1,2)	SL12M	SI12C
SL12H (1,2)	SK12C	SK12C
SJ12M (1)	SJ12M	SS12C
SJ12H (1)	SJ12H	SU12C
SM14M (1,2)	SM14M	SJ14C
SM14H (1,2)	SM14H	SR14C
SM14HH (1,2)	SM14HH	SU14C
SM16MO (2)	SW16MS	SG16S
SM16HO (2)	SW16HS	SP16S
SM16M (2)	SW16MC	SK16C
SM16H (2)	SW16HC	SR16C
SM20M	SW20M	SK20C
SM20H	SW20H	SR20C
SM24M	SW24M	SK24C
SM24H	SW24H	SR24C
SM28H	SW28H	SR28C

V24.1b

- (1) CF8M (316 SS) Impellers Standard* (2) CF8M (316 SS) Bowls Available*

In January 2018, Simmons Pump and Simflo Pumps, Inc. merged to become SIMFLO. The chart above provides a cross reference for model designations from before and after the merger.

^{*}Subject to change without notice, please consult factory for availability.




1160 RPM Selection Chart

Model Number	Bowl Dia. (in.)	Peak Eff. (full dia.)	BEP Flow (gpm)	BEP Head (ft./ stage)	BEP NPSHr (full dia.)	POR (gpm)	Ns	Nss
SR11MO	11.50	81.1	620	28.6	6.62	434-743	2333	6997
SR11HO	11.50	83.0	763	31.8	8.36	534-915	2395	6514
SP11L	11.25	84.8	726	23.8	7.85	508-871	2899	6666
SP11M	11.25	84.7	805	24.9	7.26	563-965	2949	7436
SP11H	11.25	83.3	1021	25.0	7.32	714-1225	3311	8328
SW12L	11.63	85.3	336	30.4	3.12	235-403	1644	9069
SW12M	11.63	85.3	401	35.9	2.99	281-481	1584	10215
SL12M	11.75	83.0	518	27.8	3.47	363-622	2180	10383
SL12H	11.75	82.4	582	31.3	7.09	407-698	2117	6438
SJ12M	12.00	83.4	844	31.1	8.36	591-1013	2562	6854
SJ12H	12.00	81.5	982	34.2	10.9	687-1178	2571	6079
SM14M	14.00	84.4	1561	34.0	8.90	1184-2030	3253	8894
SM14H	14.00	84.2	1865	36.1	11.7	1367-2344	3405	7940
SM14HH	14.00	83.2	1941	38.9	9.77	1359-2329	3280	9245
SM16MO	15.25	86.4	2461	42.0	11.9	1722-2953	2487	8964
SM16HO	15.25	86.6	2959	44.5	13.8	2071-3550	3661	8784
SM16M	15.25	84.4	2604	39.7	14.6	1822-3124	3740	7939
SM16H	15.25	86.5	3025	46.3	12.8	2118-3630	3594	9441
SM20M	19.25	84.3	4123	67.7	20.8	2886-4947	3157	7649
SM20H	19.25	84.8	4566	70.8	21.9	3196-5479	3213	7731
SM24M	24.00	82.3	6726	79.7	25.5	4708-8071	3568	8393
SM24H	24.00	85.3	8999	90.3	35.2	6299-10799	3755	7619
SM28H	28.00	87.8	14632	117.0	39.3	10242-17558	3943	9110

V23.1

SR11MO

1160 RPM



		US GALLONS	T EIX IVIII VO	16			
Impeller Type	Semi-Open	Bowl OD (in.)	11.50	PEI cl	N/A	Qty.	Eff.
Impeller Model	SR11MO	Thd'd Discharge Size	6" / 8" / 10"	Ns	2333	Stages	Change
One Stage Weight (lb)	270.00	Thd'd Suction Size	8"	Nss	6997	1	-3
Add'l Stage Wt. (lb)	100.00	Bell Suction Size	11.38"	Shaft Size (in.)	1.6875	2	-2
Impeller Wt. (lb)	8.00	Sub. Mtr. Size	N/A	Lateral (in)	1.13	3	-1
Std. Impeller Mtrl.	C95500	C.I. Bowl Rating (psi)	596	Setting (in)	.02	4	0
One Stage Length (in)	~25.813	D.I. Bowl Rating (psi)	Δ	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	9.50	S.S. Bowl Rating (psi)	Δ	Imp. WR ² (lb-ft ²)	.375		


Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SR11HO

1160 RPM




Impeller Type	Enclosed	Bowl OD (in.)	11.50	PEI cl	N/A	Qty.	Eff.
Impeller Model	SR11HO	Thd'd Discharge Size	6" / 8" / 10"	Ns	2395	Stages	Change
One Stage Weight (lb)	270.00	Thd'd Suction Size	8"	Nss	6514	1	-3
Add'l Stage Wt. (lb)	100.00	Bell Suction Size	11.38"	Shaft Size (in.)	1.6875	2	-2
Impeller Wt. (lb)	8.35	Sub. Mtr. Size	N/A	Lateral (in)	.72	3	-1
Std. Impeller Mtrl.	C95500	C.I. Bowl Rating (psi)	596	Setting (in)	.02	4	0
One Stage Length (in)	~25.813	D.I. Bowl Rating (psi)	Δ	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	9.50	S.S. Bowl Rating (psi)	Δ	Imp. WR² (lb-ft²)	.411		

Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SP11L 1160 RPM



Impeller Type	Enclosed	Bowl OD (in.)	11.25	PEI cl	N/A	Qty.	Eff.
Impeller Model	SP11L	Thd'd Discharge Size	6" / 8" / 10"	Ns	2899	Stages	Change
One Stage Weight (lb)	290.00	Thd'd Suction Size	8"	Nss	6666	1	-4
Add'l Stage Wt. (lb)	105.00	Bell Suction Size	11.38"	Shaft Size (in.)	1.9375	2	-3
Impeller Wt. (lb)	16.40	Sub. Mtr. Size	N/A	Lateral (in)	1.13	3	-2
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	427	Setting (in)	.125	4	-1
One Stage Length (in)	~27.50	D.I. Bowl Rating (psi)	∆925	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	10.00	S.S. Bowl Rating (psi)	∆996	Imp. WR² (Ib-ft²)	.754		


 Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SP11M

1160 RPM



Impeller Type	Enclosed	Bowl OD (in.)	11.25	PEI cl	N/A	Qty.	Eff.
Impeller Model	SP11M	Thd'd Discharge Size	6" / 8" / 10"	Ns	2949	Stages	Change
One Stage Weight (lb)	290.00	Thd'd Suction Size	8"	Nss	7436	1	-3
Add'l Stage Wt. (lb)	105.00	Bell Suction Size	11.38"	Shaft Size (in.)	1.9375	2	-2
Impeller Wt. (lb)	14.30	Sub. Mtr. Size	N/A	Lateral (in)	1.13	3	-1
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	427	Setting (in)	.125	4	0
One Stage Length (in)	~27.50	D.I. Bowl Rating (psi)	∆925	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	10.00	S.S. Bowl Rating (psi)	∆996	Imp. WR² (Ib-ft²)	.670		


 Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SP11H






Impeller Type	Enclosed	Bowl OD (in.)	11.25	PEI cl	N/A	Qty.	Eff.
Impeller Model	SP11H	Thd'd Discharge Size	6" / 8" / 10"	Ns	3311	Stages	Change
One Stage Weight (lb)	290.00	Thd'd Suction Size	8"	Nss	8328	1	-3
Add'l Stage Wt. (lb)	105.00	Bell Suction Size	11.38"	Shaft Size (in.)	1.9375	2	-2
Impeller Wt. (lb)	14.90	Sub. Mtr. Size	N/A	Lateral (in)	1.13	3	-1
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	427	Setting (in)	.125	4	0
One Stage Length (in)	~27.50	D.I. Bowl Rating (psi)	∆925	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	10.00	S.S. Bowl Rating (psi)	∆996	Imp. WR² (lb-ft²)	.718		

 Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SW12L 1160 RPM



		00 0/1220110		· -			
lesses all and Trees a	I =	David OD (in)	44.00	DEL -I	N1/A		
Impeller Type	Enclosed	Bowl OD (in.)	11.63	PEI cl	N/A	Qty.	Eff.
Impeller Model	SW12L	Thd'd Discharge Size	6" / 8" / 10"	Ns	1644	Stages	Change
One Stage Weight (lb)	235.00	Thd'd Suction Size	8"	Nss	9069	1	-3
Add'l Stage Wt. (lb)	105.00	Bell Suction Size	11.38"	Shaft Size (in.)	1.6875	2	-2
Impeller Wt. (lb)	13.80	Sub. Mtr. Size	N/A	Lateral (in)	1.13	3	-1
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	526	Setting (in)	.25	4	0
One Stage Length (in)	~26.50	D.I. Bowl Rating (psi)	∆1140	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	9.00	S.S. Bowl Rating (psi)	∆1227	Imp. WR² (lb-ft²)	.642		


Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SW12M

1160 RPM




Impeller Type	Enclosed	Bowl OD (in.)	11.63	PEI cl	N/A	Qty.	Eff.
Impeller Model	SW12L	Thd'd Discharge Size	6" / 8" / 10"	Ns	1584	Stages	Change
One Stage Weight (lb)	235.00	Thd'd Suction Size	8"	Nss	10215	1	-3
Add'l Stage Wt. (lb)	105.00	Bell Suction Size	11.38"	Shaft Size (in.)	1.6875	2	-2
Impeller Wt. (lb)	13.80	Sub. Mtr. Size	N/A	Lateral (in)	1.13	3	-1
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	526	Setting (in)	.25	4	0
One Stage Length (in)	~26.50	D.I. Bowl Rating (psi)	∆1140	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	9.00	S.S. Bowl Rating (psi)	∆1227	Imp. WR ² (lb-ft ²)	.642		

 Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SL12M1160 RPM




Impeller Type	Enclosed	Bowl OD (in.)	11.75	PEI cl	N/A	Qty.	Eff.
Impeller Model	SL12M	Thd'd Discharge Size	6" / 8" / 10"	Ns	2180	Stages	Change
One Stage Weight (lb)	250.00	Thd'd Suction Size	8"	Nss	10383	1	-3.5
Add'l Stage Wt. (lb)	107.00	Bell Suction Size	11.38"	Shaft Size (in.)	1.6875	2	-2
Impeller Wt. (lb)	13.20	Sub. Mtr. Size	N/A	Lateral (in)	1.13	3	-1
Std. Impeller Mtrl.	C95500	C.I. Bowl Rating (psi)	549	Setting (in)	.25	4	0
One Stage Length (in)	~27.50	D.I. Bowl Rating (psi)	∆1190	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	10.00	S.S. Bowl Rating (psi)	∆ 1282	Imp. WR² (lb-ft²)	.670		

 Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SL12H 1160 RPM




Impeller Type	Enclosed	Bowl OD (in.)	11.75	PEI cl	N/A	Qty.	Eff.
Impeller Model	SL12H	Thd'd Discharge Size	6" / 8" / 10"	Ns	2117	Stages	Change
One Stage Weight (lb)	250.00	Thd'd Suction Size	8"	Nss	6438	1	-1
Add'l Stage Wt. (lb)	107.00	Bell Suction Size	11.38"	Shaft Size (in.)	1.6875	2	0
Impeller Wt. (lb)	13.50	Sub. Mtr. Size	N/A	Lateral (in)	1.13	3	0
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	549	Setting (in)	.25	4	0
One Stage Length (in)	~27.50	D.I. Bowl Rating (psi)	∆1190	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	10.00	S.S. Bowl Rating (psi)	∆1 282	Imp. WR ² (Ib-ft ²)	.744		

Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SJ12M1160 RPM




Impeller Type	Enclosed	Bowl OD (in.)	12.00	PEI cl	N/A	Qty.	Eff.
Impeller Model	SJ12M	Thd'd Discharge Size	6" / 8" / 10"	Ns	2562	Stages	Change
One Stage Weight (lb)	270.00	Thd'd Suction Size	8"	Nss	6854	1	-2
Add'l Stage Wt. (lb)	110.00	Bell Suction Size	11.38"	Shaft Size (in.)	1.6875	2	-1
Impeller Wt. (lb)	17.00	Sub. Mtr. Size	N/A	Lateral (in)	1.19	3	0
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	487	Setting (in)	.19	4	0
One Stage Length (in)	~28.25	D.I. Bowl Rating (psi)	∆1056	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	10.75	S.S. Bowl Rating (psi)	Δ	Imp. WR² (lb-ft²)	.744		

 Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SJ12H1160 RPM



Impeller Type	Enclosed	Bowl OD (in.)	12.00	PEI cl	N/A	Qty.	Eff.
Impeller Model	SJ12H	Thd'd Discharge Size	6" / 8" / 10"	Ns	2571	Stages	Change
One Stage Weight (lb)	270.00	Thd'd Suction Size	8"	Nss	6176	1	-1
Add'l Stage Wt. (lb)	110.00	Bell Suction Size	11.38"	Shaft Size (in.)	1.6875	2	0
Impeller Wt. (lb)	12.00	Sub. Mtr. Size	N/A	Lateral (in)	1.19	3	0
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	487	Setting (in)	.19	4	0
One Stage Length (in)	~28.25	D.I. Bowl Rating (psi)	∆1056	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	10.75	S.S. Bowl Rating (psi)	Δ	Imp. WR² (lb-ft²)	.744		


 Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SM14M





Impeller Type	Enclosed	Bowl OD (in.)	14.00	PEI cl	N/A	Qty.	Eff.
Impeller Model	SM14M	Thd'd Discharge Size	10" / 12"	Ns	3253	Stages	Change
One Stage Weight (lb)	550.00	Thd'd Suction Size	10"	Nss	8894	1	-3
Add'l Stage Wt. (lb)	235.00	Bell Suction Size	13.88"/18.13"	Shaft Size (in.)	2.1875	2	-1
Impeller Wt. (lb)	31.70	Sub. Mtr. Size	N/A	Lateral (in)	1.25	3	0
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	459	Setting (in)	.25	4	0
One Stage Length (in)	~32.50	D.I. Bowl Rating (psi)	∆869	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	13.50	S.S. Bowl Rating (psi)	∆936	Imp. WR ² (lb-ft ²)	2.182		


Δ Consult factory for availability

Rev. 2024.01.15

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SM14H





Impeller Type	Enclosed	Bowl OD (in.)	14.00	PEI cl	N/A	Qty.	Eff.
Impeller Model	SM14H	Thd'd Discharge Size	10" / 12"	Ns	3405	Stages	Change
One Stage Weight (lb)	550.00	Thd'd Suction Size	10"	Nss	7940	1	-2
Add'l Stage Wt. (lb)	235.00	Bell Suction Size	13.88"/18.13"	Shaft Size (in.)	2.1875	2	-1
Impeller Wt. (lb)	29.00	Sub. Mtr. Size	N/A	Lateral (in)	1.25	3	0
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	459	Setting (in)	.25	4	0
One Stage Length (in)	~32.50	D.I. Bowl Rating (psi)	∆869	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	13.50	S.S. Bowl Rating (psi)	∆936	Imp. WR² (Ib-ft²)	2.023		


Δ Consult factory for availability

Rev. 2024.01.15

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SM14HH

1160 RPM



Impeller Type	Enclosed	Bowl OD (in.)	14.00	PEI cl	N/A	Qty.	Eff.
Impeller Model	SM14HH	Thd'd Discharge Size	10" / 12"	Ns	3280	Stages	Change
One Stage Weight (lb)	540.00	Thd'd Suction Size	10"	Nss	9245	1	-2.5
Add'l Stage Wt. (lb)	225.00	Bell Suction Size	13.88"/18.13"	Shaft Size (in.)	2.1875	2	-1.5
Impeller Wt. (lb)	28.40	Sub. Mtr. Size	N/A	Lateral (in)	1.25	3	-0.5
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	459	Setting (in)	.25	4	0
One Stage Length (in)	~32.50	D.I. Bowl Rating (psi)	∆869	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	13.50	S.S. Bowl Rating (psi)	∆936	Imp. WR² (lb-ft²)	2.30		


Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SM16MO

1160 RPM



Add'l Stage Length (in) Δ Consult factory for availability ~41.75

15.00

0

5


2.26

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

∆1033 Imp. WR² (lb-ft²)

S.S. Bowl Rating (psi)

SM16HO 1160 RPM



Impeller Type	Semi-Open	Bowl OD (in.)	15.25	PEI cl	N/A	Qty.	Eff.
Impeller Model	SM16HO	Thd'd Discharge Size	12" / 14"	Ns	3661	Stages	Change
One Stage Weight (lb)	600.00	Thd'd Suction Size	12"	Nss	8784	1	-3
Add'l Stage Wt. (lb)	250.00	Bell Suction Size	15.25"/19.25"	Shaft Size (in.)	2.1875	2	-2
Impeller Wt. (lb)	21.40	Sub. Mtr. Size	N/A	Lateral (in)	1.25	3	-1
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	506	Setting (in)	.02	4	0
One Stage Length (in)	~41.75	D.I. Bowl Rating (psi)	Δ	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	15.00	S.S. Bowl Rating (psi)	Δ1033	Imp. WR² (lb-ft²)	2.24		


 Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SM16M

1160 RPM




Impeller Type	Enclosed	Bowl OD (in.)	15.25	PEI cl	N/A	Qty.	Eff.
Impeller Model	SM16M	Thd'd Discharge Size	12" / 14"	Ns	3740	Stages	Change
One Stage Weight (lb)	600.00	Thd'd Suction Size	12"	Nss	7939	1	-3
Add'l Stage Wt. (lb)	250.00	Bell Suction Size	15.25"/19.25"	Shaft Size (in.)	2.1875	2	-2
Impeller Wt. (lb)	32.40	Sub. Mtr. Size	N/A	Lateral (in)	1.25	3	-1
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	506	Setting (in)	.125	4	0
One Stage Length (in)	~41.75	D.I. Bowl Rating (psi)	Δ	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	15.00	S.S. Bowl Rating (psi)	Δ1033	Imp. WR² (lb-ft²)	4.966		

 Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SM16H 1160 RPM



Impeller Type	Enclosed	Bowl OD (in.)	15.25	PEI cl	N/A	Qty.	Eff.
Impeller Model	SM16H	Thd'd Discharge Size	12" / 14"	Ns	3594	Stages	Change
One Stage Weight (lb)	600.00	Thd'd Suction Size	12"	Nss	9441	1	-3
Add'l Stage Wt. (lb)	250.00	Bell Suction Size	15.25"/19.25"	Shaft Size (in.)	2.1875	2	-2
Impeller Wt. (lb)	30.40	Sub. Mtr. Size	N/A	Lateral (in)	1.00	3	-1
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	506	Setting (in)	.125	4	0
One Stage Length (in)	~41.75	D.I. Bowl Rating (psi)	Δ	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	15.00	S.S. Bowl Rating (psi)	∆1033	Imp. WR ² (Ib-ft ²)	4.677		


 Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SM20M

1160 RPM




Impeller Type	Enclosed	Bowl OD (in.)	19.25	PEI cl	N/A	Qty.	Eff.
Impeller Model	SM20M	Thd'd Discharge Size	Δ	Ns	3157	Stages	Change
One Stage Weight (lb)	1000.00	Thd'd Suction Size	N/A	Nss	7649	1	0
Add'l Stage Wt. (lb)	450.00	Bell Suction Size	19.25"	Shaft Size (in.)	2.4375	2	0
Impeller Wt. (lb)	101.00	Sub. Mtr. Size	N/A	Lateral (in)	1.50	3	0
Std. Impeller Mtrl.	C95500	C.I. Bowl Rating (psi)	509	Setting (in)	.125	4	0
One Stage Length (in)	~44.00	D.I. Bowl Rating (psi)	Δ	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	18.00	S.S. Bowl Rating (psi)	Δ	Imp. WR² (lb-ft²)	8.22		

Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SM20H




Impeller Type	Enclosed	Bowl OD (in.)	19.25	PEI cl	N/A	Qty.	Eff.
Impeller Model	SM20H	Thd'd Discharge Size	Δ	Ns	3213	Stages	Change
One Stage Weight (lb)	1000.00	Thd'd Suction Size	N/A	Nss	7731	1	0
Add'l Stage Wt. (lb)	450.00	Bell Suction Size	19.25"	Shaft Size (in.)	2.1875	2	0
Impeller Wt. (lb)	69.00	Sub. Mtr. Size	N/A	Lateral (in)	1.31	3	0
Std. Impeller Mtrl.	C95500	C.I. Bowl Rating (psi)	509	Setting (in)	.125	4	0
One Stage Length (in)	~44.00	D.I. Bowl Rating (psi)	Δ	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	18.00	S.S. Bowl Rating (psi)	Δ	Imp. WR² (lb-ft²)	8.210		

 Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SM24M




Impeller Type	Enclosed	Bowl OD (in.)	24.00	PEI cl	N/A	Qty.	Eff.
Impeller Model	SM24M	Thd'd Discharge Size	Δ	Ns	3568	Stages	Change
One Stage Weight (lb)	1200.00	Thd'd Suction Size	N/A	Nss	8393	1	0
Add'l Stage Wt. (lb)	625.00	Bell Suction Size	26.00"	Shaft Size (in.)	2.9375	2	0
Impeller Wt. (lb)	112.00	Sub. Mtr. Size	N/A	Lateral (in)	1.50	3	0
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	418	Setting (in)	.125	4	0
One Stage Length (in)	~49.375	D.I. Bowl Rating (psi)	Δ	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	21.00	S.S. Bowl Rating (psi)	Δ	Imp. WR² (Ib-ft²)	19.69		

 Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SM24H1160 RPM




Impeller Type	Enclosed	Bowl OD (in.)	24.00	PEI cl	N/A	Qty.	Eff.
Impeller Model	SM24H	Thd'd Discharge Size	Δ	Ns	3755	Stages	Change
One Stage Weight (lb)	1200.00	Thd'd Suction Size	N/A	Nss	7619	1	0
Add'l Stage Wt. (lb)	625.00	Bell Suction Size	26.00"	Shaft Size (in.)	2.9375	2	0
Impeller Wt. (lb)	112.00	Sub. Mtr. Size	N/A	Lateral (in)	1.50	3	0
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	418	Setting (in)	.125	4	0
One Stage Length (in)	~49.375	D.I. Bowl Rating (psi)	Δ	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	21.00	S.S. Bowl Rating (psi)	Δ	Imp. WR² (lb-ft²)	19.03		

 Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

SM28H



Impeller Type	Enclosed	Bowl OD (in.)	28.00	PEI cl	N/A	Qty.	Eff.
Impeller Model	SM28H	Thd'd Discharge Size	Δ	Ns	3943	Stages	Change
One Stage Weight (lb)	2100.00	Thd'd Suction Size	N/A	Nss	9110	1	0
Add'l Stage Wt. (lb)	1000.00	Bell Suction Size	26.00"	Shaft Size (in.)	2.9375	2	0
Impeller Wt. (lb)	218.00	Sub. Mtr. Size	N/A	Lateral (in)	0.50	3	0
Std. Impeller Mtrl.	316 SS	C.I. Bowl Rating (psi)	404	Setting (in)	0.125	4	0
One Stage Length (in)	~65.00	D.I. Bowl Rating (psi)	Δ	K-Factor (lb/ft tdh)	CURVE	5	0
Add'l Stage Length (in)	24.00	S.S. Bowl Rating (psi)	Δ	Imp. WR² (lb-ft²)	39.62		

Δ Consult factory for availability

Rev. 2022.12.29

Data reflects nominal performance and may be derated for specified ANSI/HI 14.6 acceptance grade and/or materials of construction. Consult factory. Weights and lengths listed are approximate and subject to change. Consult factory.

CONTACT US
FOR THE TOOLS AND
SERVICES YOU NEED
TO MAKE THE MOST
OF YOUR WATER

SIMFLO













LUBBOCK | 2605 INTERSTATE 27 | LUBBOCK, TX | 79404 | 806.747.3411 **WILLCOX** | 754 E MALEY ST | WILLCOX, AZ | 85643 | 520.384.2273 **SOUTHAVEN** | 8500 AARON LANE | SOUTHAVEN, MS | 38671 | 662.793.8090